



# MTPS120 Series

## Level VI

### 120 Watt, Medical Grade Universal Input, Desktop Adapter

#### INPUT SPECIFICATIONS

All specifications are typical at nominal input, full load.

#### INPUT SPECIFICATIONS

Input Voltage	AC 100 – 240VAC
Input Frequency	50 – 60Hz
Input Current	1.4A – 0.5A
Protection	Internal Primary Current Fuse Inrush Limiting

#### OUTPUT SPECIFICATIONS

Output Voltage	See Chart
Efficiency	CEC Level VI, ErP Stage
2Protection	Short Circuit Protection Over Current Protection Over Voltage Protection Over Temperature Protection
Ripple	1 – 2 % Vp-p (max)
Hold-Up Time	10 mS (min)
Transient Response	0.5mS for 50% Load Change(typ)
Load Regulation	± 5% (typ)
Leakage Current	0.50mA @ 3 pin

#### GENERAL SPECIFICATIONS

MTBF(Calculated)	300,000 Hours Calculated hours at 25°C by Telecordia SR-332
Dielectric Withstanding Voltage	4,000 VAC Primary – Secondary
EMI Conduction & Radiation	Compliance to EN55011 Class B
Harmonic Current	Compliance to EN61000-3-2
EMS Immunity	Compliance to EN60601-1-2
Safety Approvals	CB/UL/cUL/FCC/CE/TUV



#### FEATURES

- *ES60601-1:2005 (60601 3<sup>rd</sup> EDITION)*
- *UNIVERSAL INPUT (AC100-240V)*
- *OVERVOLTAGE PROTECTION*
- *OVERCURRENT PROTECTION*
- *ROHS COMPLIANT*
- *CEC LEVEL VI*

#### ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	0°C~+40°C
Storage Temperature	-20°C ~ +80°C
Cooling.	Convection
Operating Humidity	20 – 80% Rh
Storage Humidity	10 – 90% Rh

#### MECHANICAL SPECIFICATIONS

Case Dimension	L175 x W74 x H42 (mm)
Input Configuration	IEC320-C14 Optional C6
DC Cord	18AWG Optional 16AWG
Output Connector	Mini-DIN



# MTPS120 Series

Model Number	Output Voltage	Output Current	Max Output Power
MTPS120-1210DT-3P-VI	12.0V	10.0A	120W
MTPS120-1580DT-3P-VI	15.0V	8.00A	120W
MTPS120-1963DT-3P-VI	19.0V	6.32A	120W
MTPS120-2450DT-3P-VI	24.0V	5.00A	120W
MTPS120-3633DT-3P-VI	36.0V	3.34A	120W
MTPS120-4825DT-3P-VI	48.0V	2.50A	120W

## Mechanical Drawing:

